



## Section 1 - Identification of Chemical Product and Company

Canberra Discount Chemicals  
3 Callan Street  
Mitchell, ACT 2911

Phone: (02) 6241 7119  
Fax: (02) 6253 8354

**Substance:** Mixture of liquid hydrocarbons and alcohols.  
**Trade Name:** Greaseater  
**Product Use:** Carpet cleaning preparation.  
**Creation Date:** August, 2002  
**This version issued:** July, 2009 and is valid for 5 years from this date.

Colour Code

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R11, R66, R20/21/22, R36/38. Highly flammable. Repeated exposure may cause skin dryness or cracking. Harmful by inhalation, in contact with skin, and if swallowed. Irritating to eyes and skin.

**Safety Phrases:** S20, S29, S33, S38, S24/25. When using, do not eat or drink. Do not empty into drains. Take precautionary measures against static discharges. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**SUSDP Classification:** S6

**ADG Classification:** Class 3 (FLAMMABLE LIQUID, N.O.S.)

**UN Number:** 1993

### Emergency Overview

**Physical Description & colour:** Clear, colourless liquid.

**Odour:** Characteristic xylene odour.

**Major Health Hazards:** Extended inhalation studies of butyl icinol in rats resulted in effects on lung, liver, kidneys and blood at high concentrations. In all cases, rapid recovery occurred after exposure.

### Potential Health Effects

#### Inhalation

**Short term exposure:** Available data shows that this product is harmful, but symptoms are not available.

**Long Term exposure:** No data for health effects associated with long term inhalation.

#### Skin Contact:

**Short term exposure:** Available data shows that this product is harmful, but symptoms are not available. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term exposure:** No data for health effects associated with long term skin exposure.

#### Eye Contact:

**Short term exposure:** Available data shows that this product is not harmful. However product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**Long Term exposure:** No data for health effects associated with long term eye exposure.

#### Ingestion:

**Short term exposure:** Available data shows that this product is harmful, but symptoms are not available. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term exposure:** No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Xylene is Class 3 - unclassifiable as to carcinogenicity to humans.

---

## Section 3 – Composition/Information on Ingredients

---

Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Butyl icinol	111-76-2	15	121	not set
Xylene	1330-20-7	40	350	655
Ethanol	64-17-5	20-40	1880	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

---

## Section 4 - First Aid Measures

---

### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia and is available at all times. Have this MSDS with you when you call.

**Inhalation:** If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** If significant skin contact occurs, wash gently and thoroughly with water (use non-abrasive soap if necessary) for 10 minutes or until chemical is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts). Contact a Poisons Information Centre, or call a doctor.

**Eye Contact:** Quickly and gently blot or brush away product. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water until the product is removed or until a few minutes after irritation has ceased, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

---

## Section 5 – Fire Fighting Measures

---

**Fire and Explosion Hazards:** This product is classified as a C1 combustible product. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and and breathing apparatus.

**Flash point:** Calculated About 15-20°C

**Upper Flammability Limit:** 19% (ethanol)

**Lower Flammability Limit:** 3.5% (ethanol)

**Autoignition temperature:** No data.

**Flammability Class:** C1

## MATERIAL SAFETY DATA SHEET

---

## Section 6 – Accidental Release Measures

---

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including face mask, face shield and gauntlets. All skin areas should be covered. See above under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

---

## Section 7 – Handling and Storage

---

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this class of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Materials to avoid" in Section 10. If you keep more than 100L of flammable liquids of Packaging Groups I and or II, you probably require a license to do so. If you have any doubts, we suggest you contact your licensing authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

---

## Section 8 Exposure Controls and Personal Protection

---

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

<b>SWA Exposure Limits</b>	<b>TWA (mg/m<sup>3</sup>)</b>	<b>STEL (mg/m<sup>3</sup>)</b>
Butyl icinol	121	not set
Xylene	350	655
Ethanol	1880	not set

**Ventilation:** No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that dusts are minimised.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: rubber, PVC.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

---

## Section 9 - Physical and Chemical Properties:

---

<b>Physical Description &amp; colour:</b>	Clear, colourless liquid.
<b>Odour:</b>	Characteristic xylene odour.
<b>Boiling Point:</b>	78°C (ethanol component only).
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	No specific data. Expected to be about 30% at 100°C.

### MATERIAL SAFETY DATA SHEET

Vapour Pressure:	No data.
Vapour Density:	No data.
Specific Gravity:	No data.
Water Solubility:	Emulsifiable.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water distribution:	No data
Autoignition temp:	No data.

---

## Section 10 – Stability and Reactivity

---

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** Keep away from heat, flames and sparks. Keep away from sources of sparks or ignition.

**Incompatibilities:** oxidising agents.

**Fire Decomposition:** Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product is unlikely to undergo polymerisation processes.

---

## Section 11 – Toxicological Information

---

**Local Effects:**

**Target Organs:** There is no data to hand indicating any particular target organs.

### Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Butyl Icinol	~12.5%Conc≤20%: Xn; R20/21/22
Xylene	Conc≥20%: Xn; R20/21; R38

---

## Section 12 – Ecological Information

---

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

---

## Section 13 – Disposal Considerations

---

**Disposal:** Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Please do NOT dispose into sewers or waterways.

---

## Section 14 – Transport Information

---

**ADG Code:** 1993, FLAMMABLE LIQUID, N.O.S.

**Hazchem Code:** 3YE

**Special Provisions:** 274

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

**Packaging Group:** II

**Packaging Method:** P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

### MATERIAL SAFETY DATA SHEET

## Section 15 – Regulatory Information

**AICS:** All of the significant ingredients in this formulation are to be found in the public AICS Database.

## Section 16 – Other Information

**This MSDS contains only safety-related information. For other data see product literature.**

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Number</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons
<b>UN Number</b>	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS copyright © Kilford & Kilford Pty Ltd, July, 2009.

<http://www.kilford.com.au> Phone (02)9251 4532

### MATERIAL SAFETY DATA SHEET